Connection elements, selection criteria

| recommended | suitable unsuitable | | († 1 💿 | | | | | | |
|-------------|--|-------------------------|-------------------|------------------|------------|-----------------|-------------|------------|-------------------|
| | | Tensioning connector | Slot connector | Inner bracket | Bracket | Central bolt | T-connector | | Bolt connector |
| L. | High feed force | | | \bigcirc | | | | | |
| | High moment | \bigcirc | \bigcirc | \bigcirc | | \bigcirc | \bigcirc | \bigcirc | |
| | High torsional moment | 0 1 | ₽€) | \bigcirc | \bigcirc | \bigcirc | | \bigcirc | |
| Þ | Minimal finishing | | | | | M12 - 9,8 • | | D17 • | D17 • |
| | Minimal assembly | | | | | | \bigcirc | | \bigcirc |
| 599 | Low parts costs | \bigcirc | \bigcirc | \bigcirc | \bigcirc | | \bigcirc | | \bigcirc |
| | Subsequent mounting in closed frame | \bigcirc | \bigcirc | \bigcirc | | \bigcirc | \bigcirc | \bigcirc | |
| | Adjustment possible | | | \bigcirc | | \bigcirc | | | |
| | Mounting of panel elements | \bigcirc | \bigcirc | \bigcirc | \bigcirc | | \bigcirc | | \bigcirc |
| | Internal connection (concealable) | | \bigcirc | | \bigcirc | | \bigcirc | \bigcirc | \bigcirc |

3